

EDR 型磁芯
EDR CORES




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7

規格 (Type)	尺寸(Unit : mm)										圖形	磁芯參數				單重 (g/prs)	Al-value (nH/N ²)							
	A	B	C	C1	C2	D	E	E1	F	G		C1 (mm ⁻¹)	Le (mm)	Ae (mm ²)	Ve (mm ³)		GP4	GP44	GP47	GP90	GP95	GP95B	GP96	
EDR2608	26.0±0.50	4.15±0.15	13.5±0.50			10.4min	21.7±0.3	2.7±0.2	2.8±0.15		Fig.1	0.34	20.19	58.59	1365.6	10.4	4200	4300	4400	4100	4900	4900	4900	
EDR2609	26.0±0.50	4.6±0.2	13.5±0.50			10.4min	21.7±0.3	2.7±0.2	2.7±0.2		Fig.1	0.344	20.19	58.59	1365.6	12.5	4000	4000	4400	4100	6000	6000	6000	
EDR2809	28.0±0.3	4.65±0.2	13.9±0.3			3.2±0.25	10.5min		3.1±0.20	25.3±0.3	Fig.2	0.578	42.3	73.2	3096	13	3500	3600	3700	3400	4300	4300	4300	
EDR2810	28.0±0.5	5.1±0.15	13.6±0.3			3.2±0.25	10.7±0.6		3.6±0.25	25.3±0.3	Fig.2	0.578	42.3	73.2	3096	13.8	3500	3500	3700	3400	4600	4600	4600	
EDR3209	32.0±0.4	4.4±0.2	11.7±0.4			27.8±0.2	8.9±0.2		2.95±0.2	2.2±0.2	Fig.7	0.27	22.42	82.77	1856.37	11.7	4500	5700	5800	5450	6500	6500	6500	
EDR3909	13.5±0.3	4.65±0.15	38.9+0.5/-0.6	38.4+0.5/-0.6	34.8+0.2/-0.6	2.75±0.15	10.6±0.3		3.0±0.15		Fig.5	0.26	102.3	23.9	2647	17		7000						
EDR39B-8.6	39.0±0.55	4.3±0.2	15.0±0.4			12.3±0.4	34.8±0.45	2.7±0.2	2.8±0.2		Fig.6	0.256	25.2	92.39	2480	17.7		6500						
EDR40	40.3±0.5	4.75±0.15	13.6+0.15/-0.4			3.15±0.15	10.9±0.3		3.25±0.15	1.30±0.15	Fig.4	0.22	25.04	115.4	2890	17.7		6000						
EDR4110	41.3±0.5	5.1±0.15	19.6±0.4			37.2±0.35	14.7min		3.05±0.2	4.5±0.25	Fig.3			158.2		33.4	9500							
EDR4111	41.3±0.5	5.65±0.15	19.6±0.4			37.2±0.35	14.7min		3.15±0.2	4.5±0.25	Fig.3	0.185	33.02	178.2	5883.4	33.4	8300	8300	9900	9300	9500	9500	9500	
EDR5111	50.8±0.8	5.6±0.15	19.8±0.4			48.5±0.5	15.0±0.6		3.3±0.2	4.6±0.35	Fig.3	0.15	32.83	220	7222.6	44.4	####	11900	12300	11300	13000	13000	13000	